

HP COMPATIBLE JD093B Quick Spec:

Part Number	JD093B
Form Factor:	SFP+
TX Wavelength:	1310nm
Reach:	300m
Cable Type:	MMF
Rate Category:	10GBase
Interface Type:	LRM
DDM:	Yes
Connector Type:	Dual-LC
Power Budget:	6.0 dB
TX Power Min/Max:	-8.00 to 0.50
RX Power Min/Max:	-14.00 to -3.00



HP COMPATIBLE JD093B Features

- Operating Data Rate up to 10.3Gbps
- 1310nm DFB-LD Transmitter
- Reach:
 - OM1 (62.5/125micron) 220m
 - OM2 (50/125micron 400 MHz*km) 100m
 - OM3 (50/125micron 500 MHz*km) 220m
 - G.652 (9/125micron singlemode) 300m
- Single 3.3V Power Supply and TTL Logic Interface
- Hot Pluggable
- Operating Case Temperature:
 - Standard: 0°C~+70°C
 - Industrial: -40°C~+85°C
- Compliant with MSA SFP+
- Compliant with IEEE 802.3ae 10GBASE-LR
- Compliant with IEEE 802.3ae 10GBASE-LW
- Compliant with SFF-8472
- RoHS 6 Compliant

HP COMPATIBLE JD093B Applications

- 10GBASE-LR at 10.3125Gbps
- 10GBASE-LW at 9.953Gbps
- Other Optical Links

HP COMPATIBLE JD093B Specification

Electrical Characteristics (Condition: Ta=TOP)

Parameter	Symbol	Min.	Typ	Max.	Unit	Notes
CML Inputs(Differential)	Vin	150		1200	mV p-p	AC coupled inputs
Supply Current	ICC			300	mA	
Input Impedance (Differential)	Zin	85	100	115	ohm	Rin > 100 kohm @ DC
Tx_Disable Input Voltage – Low	VIL	0		0.8	V	
Tx_Disable Input Voltage – High	VIH	2.0		3.45	V	
Tx_Fault Output Voltage – Low	VOL	0		0.5	V	
Tx_Fault Output Voltage – High	VOH	2.0		Vcc+0.3	V	
CML Outputs (Differential)	Vout	350		700	mV pp	AC coupled outputs
Output Impedance (Differential)	Zout	85	100	115	ohms	
Rx_LOS Output Voltage- Low	VOL	0		0.5	V	
Rx_LOS Output Voltage- High	VOH	2.5			V	

Optical Characteristics (Condition: Ta=TOP)

TX					
Parameter	Symbol	Min	Typ	Max	Unit
Data Rate		-	10.3	-	Gb/s
9µm Core Diameter SMF			10		Km
Centre wavelength	λ_c	1270	1310	1355	nm
Output Spectral Width(-20dB)	$\Delta\lambda$	-	-	1	nm
Average Output Power	P_{out}	-8	-	+0.5	dBm
Extinction Ratio	ER	3.5	-	-	dB
Average Power of OFF Transmitter				-30	dBm
Side Mode Suppression Ratio	SMSR	30			dB
Input Differential Impedance	Z_{in}	90	100	110	Ω
TX Disable	Disable		2.0	$V_{cc}+0.3$	V
	Enable		0	0.8	
TX Fault	Fault		2.0	$V_{cc}+0.3$	V
	Normal		0	0.8	
TX Disable Assert Time	t_{off}			10	us
RX					
Parameter	Symbol	Min	Typ	Max	Unit
Center Wavelength	λ_c	1260		1565	nm
Receive Sensitivity	P_{in}	-	-	-14	dBm
Maximum Input Power	P_{MAX}	-3	0	-	dBm
Signal Detect Threshold-Assertion:	SD_{HIGH}	-	-	-15	dBm
Signal Detect Threshold-Deassertion:	SD_{LOW}	-25	-	-	dBm
Output Differential Impedance	P_{in}	90	100	110	Ω
Receiver Overload	P_{max}	0.5			dBm
Optical Return Loss	ORL			-12	dB
LOS	High		2.0	$V_{cc}+0.3$	V
	Low		0	0.8	

Absolute Maximum Ratings ($T_C=25^\circ\text{C}$)

Parameter	Symbol	Min	Max	Unit
Storage Temperature	T_{ST}	-40	+85	$^\circ\text{C}$
Operating Temperature (Standard)	T_{IP}	0	+70	$^\circ\text{C}$
Operating Temperature (Industrial)		-40	+85	
Input Voltage	T_{CC}	0	5	V

Recommend Operation Environment

Parameter	Symbol	Min	Typ	Max	Unit
Supply Voltage	V_{CC}	+3.15	3.3	+3.45	V
Operating Temperature	T_{OP}	0	-	+70	$^\circ\text{C}$
Operating Temperature		-40	-	+85	