EX-XFP-10GE-ER

Hot Pluggable, Dual-LC, 1550nm, SMF, 40km, Juniper Compatible

Part Number: EX-XFP-10GE-ER

Quick Spec:

Manufacturer Compatibility:	Juniper
Form Factor:	XFP
TX Wavelength:	1550nm
Reach:	40km
Cable Type:	SMF
Rate Category:	10GBase
Interface Type:	ER
Digital Optical Mon. (DOM):	True
Connector Type:	Dual-LC

Features

- Compliant with SFF-8413 and IEE802.3ae
- Data rate selectable ≤4.25Gbps or 9.95Gbps to 10.3Gbps bit rates
- Cooled EML transmitter and PIN receiver
- Low Power Dissipation 1.5W Maximum
- -5ºC to 70ºC Operating Case Temperature
- Single 3.3V power supply
- Voltages, laser bias current, transmit optical power, receive optical power

Applications

- 10GBASE-ER at 10.3125Gbps
- 10GBASE-EW at 9.953Gbps
- Other Optical Links

Electrical Characteristics (Condition: Ta=TOP)

Parameter	Symbol	Min.	Typ	Max.	Unit	Notes
CML Inputs(Differential)	Vin	150		1200	mV p-p	AC coupled inputs
Supply Current	ICC			300	mA	
Input Impedance (Differential)	Zin	85	100	115	ohm	Rin > 100 kohm @ DC
Tx_Disable Input Voltage – Low	VIL	0		0.8	V	
Tx_Disable Input Voltage – High	VIH	2.0		3.45	V	
Tx_Fault Output Voltage – Low	VOL	0		0.5	V	
Tx_Fault Output Voltage – High	VOH	2.0		Vcc+0.3	V	
CML Outputs (Differential)	Vout	350		700	mV pp	AC coupled outputs
Output Impedance (Differential)	Zout	85	100	115	ohms	
Rx_LOS Output Voltage- Low	VOL	0		0.5	V	
Rx_LOS Output Voltage- High	VOH	2.5			V	

FluxLight, Inc.

Tel: 888-874-7574 Fax: 866-267-3045

E-mail: sales@fluxlight.com Http://www.fluxlight.com

Optical Characteristics (Condition: Ta=TOP)

TX

Parameter		Symbol	Min	Typ	Max	Unit
Data Rate			-	10.3	-	Gb/s
9μm Core Diameter SMF				10		Km
Centre wavelength		λc	1530	1550	1565	nm
Output Spectral Width(-20dB)		Δλ	-	-	1	nm
Average Output Power		P_{out}	-3	-	+3	dBm
Extinction Ratio		ER	6	-	-	dB
Average Power of OFF Transmitter					-30	dBm
Side Mode Suppression Ratio		SMSR	30			dB
Input Differential Impedance		Zin	90	100	110	Ω
TX Disable	Disable		2.0		Vcc+0.3	V
	Enable		0		0.8	
TX Fault	Fault		2.0		Vcc+0.3	V
	Normal		0		0.8	
TX Disable Assert Time		t_off			10	us

RX

Parameter		Symbol	Min	Typ	Max	Unit
Center Wavelength		λc	1530		1565	nm
Receive Sensitivity		P_{in}	-	-	-14.1	dBm
Maximum Input Power		P_{MAX}	-1.0	0	-	dBm
Signal Detect Threshold-Assertion:		SD_{HIGH}	-	-	-16	dBm
Signal Detect Threshold-Deassertion:		SD_{LOW}	-25	-	-	dBm
Output Differential Impedance		Pin	90	100	110	Ω
Receiver Overload		Pmax	0.5			dBm
Optical Return Loss		ORL			-16	dB
LOS	High	2.0			Vcc+0.3	V
	Low	0			0.8	

Absolute Maximum Ratings (T_C=25℃)

Parameter	Symbol	Min	Max	Unit
Storage Temperature	T_{ST}	-40	+85	℃
Operating Temperature (Com)	T_{IP}	0	+70	℃
Operating Temperature (Ext)		-40	+85	
Input Voltage	T_{CC}	0	5	V

Recommend Operation Environment

Parameter	Symbol	Min	Typ	Max	Unit
Supply Voltage	V_{CC}	+3.15	3.3	+3.45	V
Operating Temperature	T_{OP}	0	-	+70	℃
Operating Temperature		-40	-	+85	